

Setting New Standards Worldwide
Turf Industry Leaders in Service and Innovation





WE'RE COMMITTED TO IMPROVING YOUR HARVEST.

Features:

- New lighter weight floating cutting head for improved turf quality and less waste
- Uncluttered see-through design for easy maintenance and operation
- Can harvest 16", 18", or 24" widths in 18" to 100" lengths. Rolls or Slabs
- Optional brush attachment keeps turf free of debris and clippings
- · Quick, easy cut-off spring tension adjustment
- New exclusive Brouwer low-profile rubber mat with polyethylene sliders is gentle on turf
- · No waste: cuts close to pipes, fences and ditches
- · Optional 4 wheel drive
- Optional Auto-Steer with on-the-go microadjustment to increase turf yield per acre
- · Conveyor front weight bar, standard
- Independently mounted Curved or Cross Conveyor
- · Hydraulic flap control (Roll)



WIDTH OF CUT

12" (305mm) 16" (406mm) 18" (457mm) 23" (584mm) 24" (610mm)

LENGTH OF CUT

24" (610 mm) to 100" (2540 mm)

PERFORMANCE

1500 sq. yd. (1260 m/sq.) per hour.

THICKNESS OF CUT

Power Adjustable to 2 1/8" (54 mm)

OPERATING DIMENSIONS

L.176 in.(4470 mm.) W. 120 in.(3048 mm.) H. 104 in. (2641 mm.)

WEIGHT

John Deere 2WD 11210 lbs. John Deere 4WD 11755 lbs.









KESMAC INC.

TEL: 905-476-6222 • 1-888-341-5113 FAX: 905-476-6744

US Parts TEL: 1-800-314-1008

23324 Woodbine Avenue, Keswick, Ontario L4P 3E9 email: info@kesmac.com • www.brouwerturf.com

