

# INSTALLERS

RM 2430, 2442 & 2448

LARGE ROLL TURF INSTALLER

*Setting New Standards Worldwide*  
*Turf Industry Leaders in Service and Innovation*





# YOU'LL SEE MORE BUSINESS AND A LOT FEWER SEAMS.

The ROLLMATE RM 2430, 2442 & 2448 Sod Layer is the ideal sod layer for sod growers, landscapers, rental outlets, and other contractors. The 42" or 48" wide, 4 foot 48" diameter, 2000 pound roll capacity along with the exceptional maneuverability, make the RM 2430, 2442 & 2448 an ideal choice for most sod laying applications. A reliable Honda 11.0 HP Industrial/Commercial engine drives through a field-proven infinitely variable hydrostatic drive to hydraulic motors in front wheels that shifts effortlessly from forward to reverse with a single lever control mounted on the steering handle. The sod roll can be lifted by inserting the adjustable mandrel in the sod roll which self engages onto the lift arms. The Brouwer ROLLMATE SOD LAYER is an outstanding machine for operating on slopes, highly maneuverable and easy to operate.

### RM 2430, 2442 & 2448 Features:

- Excellent for large roll installation on slopes
- Durable heavy steel frame
- Hydrostatic transmission
- Pivoting rear tire steering means minimal turf damage or scuffing, excellent maneuverability
- Easy to operate



KESMAC INC.  
 TEL: 905-476-6222 • 1-888-341-5113 FAX: 905-476-6744  
 US Parts TEL: 1-800-314-1008  
 23324 Woodbine Avenue, Keswick, Ontario L4P 3E9  
 email: info@kesmac.com • www.brouwerturf.com



### RollMate Common Specifications

Length .....	107" (271 cm)
	84" (213 cm) (Handle folded for shipping)
Height .....	45" (114 cm)
	50" (127 cm) (Handle folded for shipping)
Wheelbase .....	58" (147cm)
Ground Clearance .....	7" (17.8 cm)
Tires .....	Front: 24x12-12 turf tread Rear: 18x9.50-8 straight rib
Controls .....	F-N-R - Spring centred level to neutral. Lift Arms - Lift, lower & float level
Lift .....	2 cylinders, 2" bore x 8" stroke
Steering .....	Height adjustable handle to pivoting rear wheel
Drive .....	Infinitely variable hydrostatic drive to hydraulic motors in front wheels
Engine .....	11 hp Honda GX340, electric start
Fuel Capacity .....	1.6 gal. (6.1 liters)
Speed .....	0 - 4.7 mph (7.6 kph)
	Infinitely variable forward/reverse
Sod Roll	
Weight Capacity .....	2000 lbs (907 kg)

### Model Specific Specifications

#### ROLLMATE 2430:

Width .....	69" (175 cm)
Roll Width Capacity .....	24 & 30" (61 cm & 76 cm)
Weight .....	975 lbs. (442 kg)

#### ROLLMATE 2442:

Width .....	81" (205 cm)
Roll Width Capacity .....	42" (106 cm)
Weight .....	1090 lbs. (494 kg)

#### ROLLMATE 2448:

Width .....	87" (221 cm)
Roll Width Capacity .....	48" (122 cm)
Weight .....	1150 lbs. (522 kg)

Specifications subject to change without notice or obligation.  
 Printed in Canada 01/19